



# EVOX 5

## ACTIVE TWO-WAY ARRAY



**Description** Evox 5 is a portable compact size sound reinforcement system. Evox 5 combines the quality and reliability of RCF transducers with a very high amplification power. The system features five 2.0" full range transducers in the line source satellite and a deep sounding 10" woofer in a bass reflex enclosure. The system is designed to be the perfect portable solution for live music and DJs. The unique vocal attitude and portability make Evox 5 the perfect tool for presentations, corporate events and congresses.

- Features**
- › 800 Watt
  - › 125 dB max SPL
  - › 45 Hz 20 kHz frequency response
  - › 10" Woofer, 2.0" v.c.
  - › 5 x 2" Ultra compact fullrange, 1.0 v.c.
  - › 120° x 30° slightly tilted pattern control
  - › Innovative DSP processing
  - › Pole mountable, easy set-up and transportation

|                    |                 |           |       |                   |
|--------------------|-----------------|-----------|-------|-------------------|
| <b>Part Number</b> | 13000440 EVOX 5 | 220-240 V | Black | EAN 8024530012144 |
|                    | 13000441 EVOX 5 | 115 V     | Black | EAN 8024530012380 |



# EVOX 5

ACTIVE TWO-WAY ARRAY



Line Art 2D

## TECHNICAL SPECIFICATIONS

|                                  |                           |                          |
|----------------------------------|---------------------------|--------------------------|
| <b>Acoustical specifications</b> | Frequency Response        | 45 Hz ÷ 20000 Hz         |
|                                  | Max SPL @ 1m              | 125 dB                   |
|                                  | Horizontal coverage angle | 120°                     |
|                                  | Vertical coverage angle   | 30°                      |
| <b>Transducers</b>               | Fullrange                 | 5 x 2.0", 1.0" v.c       |
|                                  | Woofer                    | 10", 2.0" v.c            |
| <b>Input/Output section</b>      | Input signal              | bal/unbal                |
|                                  | Input connectors          | XLR, Jack                |
|                                  | Output connectors         | XLR                      |
|                                  | Input sensitivity         | -2 dBu/+4 dBu            |
| <b>Processor section</b>         | Crossover Frequencies     | 220 Hz                   |
|                                  | Protections               | Thermal, RMS             |
|                                  | Limiter                   | Soft Limiter             |
|                                  | Controls                  | Volume, EQ, Phase, Xover |
| <b>Power section</b>             | Total Power               | 800 W Peak, 400 W RMS    |
|                                  | High frequencies          | 200 W Peak, 100 W RMS    |
|                                  | Low frequencies           | 600 W Peak, 300 W RMS    |
|                                  | Cooling                   | Convection               |
|                                  | Connections               | VDE                      |
|                                  | Safety agency             | CE compliant             |
| <b>Standard compliance</b>       | Safety agency             | CE compliant             |
|                                  |                           |                          |
| <b>Physical specifications</b>   | Cabinet/Case Material     | Baltic birch plywood     |
|                                  | Hardware                  | 2 x M6                   |
|                                  | Handles                   | 1 Top                    |
|                                  | Pole mount/Cap            | Yes                      |
|                                  | Color                     | Black                    |
| <b>Size</b>                      | Height                    | 490 mm / 19.29 inches    |
|                                  | Width                     | 288 mm / 11.34 inches    |
|                                  | Depth                     | 427 mm / 16.81 inches    |
|                                  | Weight                    | 18.8 kg / 41.45 lbs      |



# EVOX 5

ACTIVE TWO-WAY ARRAY

|                    | <b>ACCESSORIES</b>   |       |                   |
|--------------------|----------------------|-------|-------------------|
| <b>Protections</b> | <b>COVERS</b>        |       |                   |
|                    | 13360304 CVR EVOX 5  | Black | EAN 8024530012342 |
| <b>Cables</b>      | <b>CABLES KIT</b>    |       |                   |
|                    | 13360102 AC XLR 3M3F |       | EAN 8024530006402 |